



Features

- Cast Iron GG20 with black bitumen painting.
- PN10, PN16 working pressure.
- Equipped with galvanized steel, bolts, washers, nuts.
- EPDM or NBR rubber seals.

Materials

N	PART NAME	MATERIAL	STANDARD
1	Center Sleeve	Cast Iron/Ductile Iron	GG20/GGG50
2	End Ring	Cast Iron/Ductile Iron	GG20/GGG50
3	Seal Ring	Rubber	EPDM
4	Bolt	Galvanized Steel	
5	Washer	Galvanized Steel	
6	Nut	Galvanized Steel	
7	Cap	Plastic	

Dimensions (mm)

PVC Pipe OD	A	C	Bolts No.	MXL	Weight (kg)
50	130	80	2	M10X160	2,2
63	137	100	2	M10X160	2,2
75	149	100	2	M10X160	2,7
90	164	120	2	M10X180	3
110	184	120	3	M10X180	4,5
125	199	120	3	M12X190	6,5
140	214	120	3	M12X190	7
160	234	140	3	M12X210	8
180	254	140	3	M12X210	10
200	274	140	3	M12X210	12
250	341	160	4	M14X240	19
315	406	160	4	M14X240	25
400	495	160	6	M14X240	30
500	600	160	6	M14X240	40