



### Generic Data

- Ductile iron body and gland GGG-50 epoxy coated
- PN 10, PN 16 working pressure.
- Equipped with steel nuts and washers with Dacromet coating.
- EPDM or NBR gasket
- High tensile resistance of the pipes.
- Angular deflection +/- 3°.

### Materials

N°	ITEM	MATERIAL	STANDARD
1	Body	Ductile Iron	GGG50
2	Joint	Rubber + Brass	EPDM + Brass
3	Gland	Ductile Iron	GGG50
4	Bolts	Dacromet coated steel	ISO898-1:1999
5	Washers	Dacromet coated steel	
6	Nuts	Dacromet coated steel	ISO898-2:1992
7	Cap	Plastic	

### Dimensions (mm)

PIPE OD	ID	A	L	QUANTITY	WEIGHT
				BOLTS	Kg
50	55	140	95	2XM12	2,73
63	67	150	95	2XM12	3,41
75	80	150	95	4XM12	4,10
90	95	180	95	4XM12	4,58
110	115	200	95	4XM12	6,34
125	130	240	95	4XM12	7,80
160	165	270	95	4XM14	9,56
200	205	325	110	4XM14	15,11
225	230	325	135	4XM14	19,01
250	255	380	135	6XM16	27,30
280	285	380	135	6XM16	29,25
315	320	420	170	6XM16	43,88